

Audio Pass Through

Allows you to listen to external speakers via the projector's audio output in Standby Mode

Long Life Filter

The projector provides users with a lower total cost of ownership by offering less frequent maintenance

Power Saving Mode

Reduces power consumption to less than 0.5W

Template Function

Four line templates in the projector can help when writing on a whiteboard

Transition Detector and Security Bar

A security sensor recognizes when the projector has been moved

Input Source Naming

Users can name sources in simple language instead of factory default name

Whiteboard Mode

Limits peak white by reducing brightness to protect eye health



Education Series

Exclusive to Hitachi



Whiteboard Mode



Template Function



IR Remote Frequency Change



Input Source Naming

Advantages

Audio Pass Through

Power Saving Mode

Template Function

Transition Detector and Security Bar

Whiteboard Mode

Input Source Naming

Easy Maintenance

Specification Highlights

3,500 ANSI Lumens

XGA Resolution (1024 x 768)

2000:1 Contrast Ratio (Using Active Iris)

8.2 Lbs.

Hybrid Filter (5,000 Hours Between Maintenance)

6,000 Hour Lamp Life (Eco Mode)*

16 Watt Audio Output

2 RGB In 1 RGB Out / Composite / S-Video / Video

USB Connection

CC1, CC2, CC3, CC4


* Actual lamp life will vary by individual lamp and based on environmental conditions, selected operating mode, user settings and usage. Hours of average lamp life specified are not guaranteed and do not constitute part of the product or lamp warranty. Lamp brightness decreases over time.

3,500 ANSI Lumens



Project a clear image in any classroom or conference room.

Hybrid Filter (5,000 Hours between maintenance)



The projector provides users with a lower total cost of ownership by offering less frequent maintenance.

6,000 Hour Lamp Life (Eco Mode)*



Another key to low total cost of ownership is a long life lamp. The lamp is rated at 3,000 hours in standard mode and 6,000 hours in Eco mode.

16 Watt Audio Output



16W Audio Output eliminates the need to connect external speakers.

Whiteboard Mode



Limits the peak white by changing the gamma curve limiting its brightness when used with a whiteboard to protect the eye health of teachers and students. **Exclusive to Hitachi.**

Input Source Naming



Users can name input sources in simple language instead of factory default name. **Exclusive to Hitachi.**

Transition Detector and Security Bar



A security sensor located inside the projector recognizes when the projector has been moved. Moving the projector without using the correct PIN Code will disable the projector.

Closed Captioning



CC1, CC2, CC3, CC4

2 RGB In 1 RGB Out / Composite / S-Video / Video




The rich connectivity allows you to connect to two computer and multiple video sources at the same time. Monitor loop-through for ease of use with desktop computers.

Power Saving Mode




The Saving Mode reduces the stand-by power consumption to 0.5W when using 120 volts with limitation of some features.

Easy Maintenance



Easy Maintenance is another attractive function, as the lamp door is on top of the model and the filter slides to the front.

Template Function



Line templates in the projector menu can help when writing on a whiteboard. There are four types of line templates to choose from. **Exclusive to Hitachi.**

IR Remote Frequency Change



To avoid conflict with fluorescent lights or IrDA (IR Signal) from notebook PC, the frequency of the IR remote control can be changed from the menu. **Exclusive to Hitachi.**

MyButton / MySource - Doc Camera



Two customizable buttons on the remote control allow users to create a shortcut for any projector command such as: Direct Input (RGB1, S-Video etc.), Picture Mode, or Filter Reset. For connection to a document camera, MySource allows users to add a third "Document Camera" source button.

PIN Lock / MyScreen / MyText



PIN lock protection can limit projector users. MyScreen PIN Lock keeps captured images on the startup screen. Users can set a school's name or company's logo to "MyScreen," clearly identifying ownership. MyText provides the ability to write text on the start up screen, such as model name, serial number, or location.

Auto Vertical Keystone



Automatic Vertical Keystone detects the angle of the projector and corrects the image.

Serial Number Label on Side



It is convenient for users or auditors to be able to check the model name and serial number of an asset easily when the product is ceiling mounted. The label is upside-down and easily viewable for ceiling-use.



Education Series

* Actual lamp life will vary by individual lamp and based on environmental conditions, selected operating mode, user settings and usage. Hours of average lamp life specified are not guaranteed and do not constitute part of the product or lamp warranty. Lamp brightness decreases over time.